

eArc

SMF520J-12X12UW

520 Watt

144 Half Cell Monocrystalline Module



Ultra-light: Glass free module weighs 7.7 kg, 70% lighter than conventional glass modules.



Fast-Installation: Through “Quick-Bonding” installation, eArc requires no penetration, reduces time on roof and saves installation costs.



Safety: Integration with underlying installation surface, ensuring the waterproof performance and safety performance of the roof.



Durable: eArc is the first glassless module to pass the same durability tests as conventional glass modules, including IEC 61215:2016, IEC61730:2016 and UL61730 (USA). eArc has also passed PID, salt mist level 8 tests.

POWER OUTPUT RANGE 520 W

POWER TOLERANCE 0-5 W

12 Year Product Warranty

25 Year Linear Power Warranty



www.sunman-energy.com




ULTRA-LIGHT&FLEXIBLE SOLAR PANEL


LINEAR PERFORMANCE WARRANTY

CAUTION:Read installation manual before using the product.


©2024 SunMan (zhenjiang) Co.,Ltd.All rights reserved.Specifications included in this datasheet are subject to change without notice.



DIMENSIONS



I-V CURVE (520)



TEMPERATURE CHARACTERISTICS

Nominal Module Operating Temperature(NMOT) **41±2 °C**

Temperature Coefficient of P_{max} **-0.34 %/°C**

Temperature Coefficient of V_{oc} **-0.26 %/°C**

Temperature Coefficient of I_{sc} **0.033 %/°C**



SMF520J-12X12UW IEC EN 2024B 9

ELECTRICAL CHARACTERISTICS

STC	SMF520J-12X12UW
Maximum Power (P_{max})	520
Maximum Power Voltage (V_{mp})	42.3
Maximum Power Current (I_{mp})	12.31
Open-circuit Voltage (V_{oc})	49.5
Short-circuit Current (I_{sc})	13.56
Module Efficiency (%)	19.3
Operating Temperature	-40 °C to 85 °C
Maximum System Voltage	1500 V DC (IEC)
Maximum Series Fuse Rating	25 A
Application Class	Class A
Power Tolerance	0/+5 W
STC: Irradiance 1000W/m², Cell temperature 25 °C, AM=1.5. Tolerances of P_{max} , V_{oc} and I_{sc} are within ±5%	

NMOT	SMF520J-12X12UW
Maximum Power (P_{max})	429.2
Maximum Power Voltage (V_{mp})	41.8
Maximum Power Current (I_{mp})	10.26
Open-circuit Voltage (V_{oc})	49.8
Short-circuit Current (I_{sc})	10.82
NMOT: Irradiance 800W/m², Ambient temperature 20 °C, AM=1.5, Wind speed 1 m/s.	

MECHANICAL CHARACTERISTICS

Solar Cell	Monocrystalline silicon(182mm half cell)
No. of Cells	144 (12×12)
Module Dimensions	2246×1197×2 mm
Weight	7.7kg ±3%
Backsheet	White
Frame	Frameless
J-box	IP 68 rated
Output Cables	Photovoltaic technology cable 4.0 mm 2, (+)450 / (-)450 mm
Connector	MC4-EVO2

PACKAGING CONFIGURATION

	20' GP	40' HC
Module per pallet	66	66&50
Pieces per container	264	828